

Technical parameter of conventional welding rotator

Spec.	Max. load weight-kg	Range of suitable strokepiece-mm	Dia. and width of the wheel		Roller linear speed-m/h	Motor power-kw	Way of setting
			Rubber roller (mm)	Metal roller (mm)			
GLHK-3	3000	φ250-φ1800	Φ200*100	2*Φ194*20	6-60	2*0.25	AC converter stepless speed adjust or electromagnetic speed adjust
GLHK-5	5000	φ250-φ2300	Φ250*100	2*Φ240*20	6-60	2*0.37	
GLHK-10	10000	φ320-φ2800	Φ300*120	2*Φ290*25	6-60	2*0.55	
GLHK-20	20000	φ500-φ3500	Φ350*120	2*Φ340*30	6-60	2*1.1	
GLHK-40	40000	φ600-φ4200	Φ400*120	2*Φ390*40	6-60	2*1.5	
GLHK-60	60000	φ750-φ4800	Φ450*120	2*Φ440*50	6-60	2*2.2	
GLHK-80	80000	φ850-φ5000	Φ500*120	2*Φ490*60	6-60	2*3	
GLHK-100	100000	φ1000-φ5500	Φ500*120	2*Φ490*70	6-60	2*3	
GLHK-160	160000	φ1100-φ6000	-	Φ620*220	6-60	2*4	
GLHK-250	250000	φ1200-φ7000	-	Φ700*280	6-60	2*5.5	
GLHK-500	500000	φ1500-φ8000	-	Φ850*350	6-60	2*7.5	
GLHK-630	630000	φ1500-φ9000	-	Φ900*380	6-60	2*11	