



# TOB BRIDGE INDUSTRY CO.,LTD.

## QUALITY CERTIFICATION FOR GOUGING CARBON

PRODUCT NAME  
Gouging carbon

Batch NO. :  
SO200906024

THE GOUGING CARBON STANDARD: JB/T8154-1999

Specification	4X355	6X355	8X355	10X355	12X355
diameter D± 3%	3.9-4.1	5.9-6.1	7.9-8.1	9.9-10.1	11.9-12.1
Length D± 3mm	355-355.5	355-355.5	355-355.5	355-355.5	355-355.5
Thickness of copper layer mm	0.052-0.063	0.065-0.07	0.07-0.09	0.09-0.11	0.12-0.13
Electrical resistance ≤23	≤18.0	≤18.0	≤18.0	≤18.0	≤18.0
ASH ≤1.5%	≤0.6	≤0.6	≤0.6	≤0.6	≤0.6
Water: <0.6	<0.6	<0.6	<0.6	<0.6	<0.6
≥17 Mpa Bending Strength(flat type ≥17m)	≥25 Mpa	≥25 Mpa	≥25 Mpa	≥25 Mpa	≥25 Mpa

Adopt the two-time sampling plan, General Inspection Level II described in GB/T2828, this batch of product had been tested well, according with the chinese gouging carbons standard.

